

## Fasteners for moulded / profile based GRP grating

### W-clip, 50 mm

Type	:	W-clip / Ø50
Diameter	:	50 mm
Hole	:	9 mm
Bolt	:	M8
Material	:	316L
Thickness of plate	:	1,5 mm
Height	:	2,5 mm
Weight	:	23 g



W-clip, Ø50 mm

### W-clip, 70 mm

Type	:	W-clip / Ø70
Diameter	:	70 mm
Hole	:	11 mm
Bolt	:	M10
Material	:	316L
Thickness of plate	:	1,5 mm
Height	:	4 mm
Weight	:	45 g



W-clip, Ø70 mm

### M-clip, 38 mm

**for moulded grating mesh 38 x 38 mm**

Type	:	M-clip - 38 mm
Opening center-center	:	38 mm
Hole	:	8,5 mm
Bolt	:	M8
Material	:	316L
Thickness of plate	:	2 mm
Width	:	20 mm
Height	:	12 mm
Weight	:	23 g



### C-clip

Type	:	C-clip w/gripclaw + W-clip
Opening	:	19 mm
Internal threads	:	8 mm
Height	:	45 mm
Width	:	30 mm
Material	:	316L
Thickness of plate	:	4 mm
Weight (C-clip only)	:	27 g



## Fasteners for moulded / profile based GRP grating

### Hilti-clip

Type	:	W-clip - Ø50
Diameter slice	:	50 mm
Internal screw-thread	:	M8
External thread diameter:	:	11 mm
Min. hole diameter	:	18 mm
Material	:	316L
Thickness of slice	:	1,5 mm
Height	:	4 mm
Weight	:	31 g



Hilti-clip w/M8x50  
headless screw



Hilti-clip w/M8  
nail for shooting



Hilti-clip w/8 mm screw auger

### Flange lock nut

Type	:	Lock nut with self-locking thread and flange with grip claws
Diameter	:	M8 eller M10
Material	:	A4
Weight	:	11g



### Storm clip

Type	:	Storm clip for 38 x 38 mm moulded grating
Lengde	:	295 mm
Bredde	:	65 mm
Height	:	25 mm
Hole	:	10,5 mm
Bolt	:	2x M10
Material	:	316L steel
Plate	:	3 mm
Weight	:	632 g

